



Laundry Machines
for any use



AQUASTAR
LAUNDRY SOLUTIONS

HIGH-SPIN Washer Extractor - Series: **MAQ2 - A**

NOT Need fixing to the floor

Our range of **High-Spin Washer Extractors** is designed to provide high performance at all times, meeting the most demanding requirements while notably reducing water and power consumption.

The savings achieved in these areas even allow us to guarantee that these appliances will pay for themselves in the medium term.

This range of high spin washer extractors includes 10, 13, 18, 25, 35, 45, 60 and 120 kg capacity appliances, with a **Programmable TOUCH SCREEN computer**.

The stylish new look and cutting-edge technology of these industrial washer extractors combines with the simplicity of their installation, and we have even reduced their size without affecting their load capacity.



- A stainless steel body, more durable and hard-wearing than painted plate, and high-quality components.
- Easier repairs, with alarm, statistics control, memory, repair kits and a drum that can be removed via the front of the appliance, reducing the minimum space and time required.
- Soft mounted machines: they do not need fixing to the floor on installation.
- New detergent compartment with non-return system.
- Easy connection for automatic product dispensing.
- Automatic unbalance detection system enabling gentler movement and prolonging the components' lifetime.
- A G factor of 350 and a spin speed of 950 - 1100 rpm, depending on the model.
- Standard frequency inverter.
- **All models are equipped of a TOUCH SCREEN Computer TC type**



- Touch Screen 4.3".
- Programmer: 33 available languages.
- USB port for washer's software updates and other applications.
- Touch Control for OPL washers and coin washers
- Delayed start. Timer (real time and date).
- 3 standard water intakes.
- Configuration of washing and spinning speed.
- Complete regulation of water levels
- Regulable washing temperature from 20°C a 90°C.
- Standard WET CLEANING system.
- Main screen display and washing process screen can be modified with parameters and images suiting each client.
- **LOADING AID** feature with water and rotation control for easy loading of the linen.

Serie: MAQ2 A - TC

		A 11	A14	A18	A25	A35	A45	A60	A120
DRUM									
Load Capacity	Kg	10	13	18	25	35	45	60	120
Drum Volume	Lt	100	130	180	250	350	450	600	1200
Basket diameter	∅	532	620	700	770	860	918	1048	1360
Depth basket	mm	425	430	470	530	602	720	684	840
Washing Speed	G/min	50	50	47	45	42,5	42,5	38	34
Extraction Speed	G/min	1245	1150	1080	1035	975	850	760	680
"G" Factor		450	450	450	450	450	350	350	350
Noise Level	Db	60	60	60	60	60	60	60	60

LOADING DOOR

Height Center door	mm	625	700	750	865	885	1118	1118	1330
Door diameter	∅	290	373	373	373	560	560	560	700

POWER

Motor power	Kw	0,75	1,5	2,2	3	4	7,5	11	15
Electric Heating	Kw	6	9	12	18	21	28,8	36	-----
Total Power for ELECTRIC Version	Kw	6,25	9,5	12,75	19	22	31,3	40	-----
Total Power for STEAM Version	Kw	0,75	1,5	2,2	3	4	7,5	11	15
Total Power for HOT WATER Version	Kw	0,75	1,5	2,2	3	4	7,5	11	15

CONNECTIONS

Drain water	∅	3"	3"	3"	3"	3"	3"	3"	4"
Water inlet	∅	3/4"	3/4"	3/4"	3/4"	3/4"	1"	1"	1 1/2"
Water Pressure	Bar	2 ÷ 4	2 ÷ 4	2 ÷ 4	2 ÷ 4	2 ÷ 4	2 ÷ 4	2 ÷ 4	2 ÷ 4
Steam Inlet (only for STEAM Version)	∅	1/2"	1/2"	1/2"	3/4"	3/4"	3/4"	3/4"	1 1/4"

MACHINE DIMENSIONS

Front Width	mm	692	788	884	979	1095	1478	1478	1836
Depth	mm	788	870	914	1041	1184	1444	1444	1863
Height	mm	1158	1301	1409	1548	1598	1905	1905	2245
NET Weight	Kg	230	250	360	490	750	1350	1400	3950

MACHINE DIMENSIONS with PACKING

Front Width	mm	730	830	930	1040	1165	1540	1540	1900
Depth	mm	1000	1010	1030	1160	1230	1580	1580	1940
Height	mm	1410	1560	1700	1850	1920	1970	1970	2290
GROSS Weight	Kg	239	283	393	545	820	1420	1520	4100
Volume	mt3	1,03	1,31	1,63	2,23	2,75	4,79	4,79	8,44